

Fuel System Water Remover

Product properties

Binds and reliably removes condensed water and moisture from the entire fuel system. Protects against rust and corrosion and increases the lifespan of the engine. Ensures a clean and powerful combustion, improves engine running and cold starting performance and optimises exhaust emission. Prevents ice formation.

Area of application

For all petrol and diesel powered engines.

Application

Add every 3-4 months to the fuel system before filling up.

Caution: Cleaning fluid – no fuel substitute! Flammable. Harmful: may cause lung damage if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. If swallowed, seek medical advice immediately and show this container or label. Keep out of reach of children.

Consumption

300 ml sufficient for 60 – 80 litres petrol fuel

Reaction time

Works during operation

Technical data

Physical state: liquid

Colour: violet

Odour: aromatic

Initial boiling point and boiling range: 145 - 200 °C

Flashpoint: 35 °C

Lower explosion limit: 0,6 Vol.-%

Upper explosion limit: 6,5 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): 4 hPa

Density at 68 °F: 0.78-0.82 g/cm³

Water resistant

Available size	Item no.	PU
300ml	33068	24
1000ml	51169	12
5L	51168	1



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.